




FLUIDJET

FL-5 BICO SPRAY - TIPO LEQUE ÂNGULO ABERTO



Fabricamos com outras especificações sob consulta



MODELO	ROSCA NPT / BSP				SAÍDA Ø mm	VAZÃO - LIT. / MIN													
	1/8"	1/4"	3/8"	1/2"		kg/cm²													
						0.7	1	1.5	2	3	4	6	7	10	15				
FL-5 / 40.01	•				0.61		0,23	0,28	0,32	0,39	0,46	0,56	0,60	0,72	0,88				
FL-5 / 40	•				0.71	0,29	0,34	0,42	0,48	0,59	0,68	0,95	1,0	1,2	1,5				
FL-5 / 41.01	•				0.84	0,38	0,46	0,56	0,64	0,79	0,91	1,1	1,2	1,4	1,8				
FL-5 / 41	•				1.0	0,57	0,68	0,84	0,97	1,2	1,4	1,8	1,9	2,3	2,8				
FL-5 / 42.01	•	•			1.2	0,76	0,91	1,1	1,3	1,6	1,8	2,4	2,6	3,1	3,8				
FL-5 / 42.02	•	•			1.3	0,95	1,1	1,4	1,6	2,0	2,3	2,8	3,0	3,6	4,4				
FL-5 / 42	•	•			1.4	1,1	1,4	1,7	1,9	2,4	2,7	3,3	3,6	4,3	5,3				
FL-5 / 43.01	•				1.7	1,5	1,8	2,2	2,6	3,2	3,6	4,5	4,8	5,8	7,1				
FL-5 / 43	•	•			1.9	1,9	2,3	2,8	3,2	3,9	4,6	5,6	6,0	7,2	8,8				
FL-5 / 44.01	•	•			2.3	2,9	3,4	4,2	4,8	5,9	6,8	7,8	8,4	10,1	12,1				
FL-5 / 44.02	•	•			2.6	3,8	4,6	5,6	6,4	7,9	9,1	11,2	12,1	14,4	17,7				
FL-5 / 44	•	•			2.9	4,6	5,5	6,7	7,7	9,5	10,9	14,0	15,1	18,0	22,0				
FL-5 / 45.01	•	•	•		3.3	5,7	6,8	8,4	9,7	11,8	13,7	16,7	18,1	22,0	26,0				
FL-5 / 45.02	•	•	•		3.6	6,9	8,2	10,0	11,6	14,2	16,4	20,0	22,0	26,0	32,0				
FL-5 / 45.03	•	•	•		3.8	7,6	9,1	11,2	12,9	15,8	18,2	21,0	23,0	27,0	34,0				
FL-5 / 45	•	•	•		4.0	8,4	10,0	12,3	14,2	17,4	20,0	26,0	28,0	33,0	41,0				
FL-5 / 46.01	•	•	•		4.1	9,2	10,9	13,4	15,5	18,9	22,0	28,0	30,0	36,0	46,0				
FL-5 / 46.02	•	•	•		4.4	10,3	12,3	15,1	17,4	21,0	25,0	31,0	33,0	39,0	50,0				
FL-5 / 46.03	•	•	•		4.6	11,4	13,7	16,7	19,3	24,0	27,0	33,0	36,0	43,0	55,0				
FL-5 / 46	•	•	•		5.0	13,3	16,0	19,5	23,0	28,0	32,0	39,0	42,0	50,0	64,0				
FL-5 / 47.01	•	•	•		5.3	15,3	18,2	22,0	26,0	32,0	36,0	44,0	47,0	56,0	71,0				
FL-5 / 47.02	•	•	•		5.6	17,2	21,0	25,0	29,0	36,0	41,0	49,9	52,5	62,7	79,8				
FL-5 / 47	•	•	•		6.0	19,1	23,0	28,0	32,0	39,0	46,0	56,0	60,0	72,0	92,0				
FL-5 / 48	•	•	•		6.5	23,0	27,0	33,0	39,0	47,0	55,0	67,0	72,0	86,0	110				
FL-5 / 49	•	•	•		7.1	27,0	32,0	39,0	45,0	55,0	64,0	78,0	83,8	100	128				
FL-5 / 50	•	•	•		7.5	31,0	36,0	45,0	52,0	63,0	73,0	89,0	95,6	114	146				

VAZÃO para AR LIT. / MIN				VAZÃO para VAPOR (quilograma por hora)			
kg/cm²				kg/cm²			
0.7	1.5	3.0	3.5	0.7	1.5	3.0	3.5
4,5	6,4	10,5	11,6	0,16	0,23	0,37	0,41
6,2	9,1	14,7	16,7	0,23	0,33	0,53	0,60
9,6	13,7	22,0	25,0	0,34	0,49	0,80	0,90
15,3	22,0	36,0	40,0	0,54	0,78	1,3	1,5
19,3	28,0	45,0	51,0	0,68	1,0	1,6	1,8
27,0	37,0	60,0	71,0	0,95	1,3	2,1	2,5
31,0	47,0	77,0	85,0	1,1	1,7	2,7	3,0
40,0	57,0	85,0	108	1,4	2,0	3,1	3,9
54,0	76,0	124	139	1,9	2,7	4,5	5,0
79,0	117	189	210	2,9	4,2	6,8	7,6
110	159	255	290	3,9	5,7	9,2	10,4
181	260	420	475	6,5	9,3	15,0	17,1
225	325	520	590	8,0	11,6	18,8	21,0
320	465	760	850	11,5	16,8	27,0	30,0

ACESSÓRIOS PARA BICOS CM; CF E FM; FF



FILTRO D'ÁGUA
TELA AÇO INOX
MALHA 30, 50, 80, 100

BICO COM FILTRO		MODELO	ÂNGULO DE PULVERIZAÇÃO	
FL-5 FM	FL-5 FF		kg/cm²	
		FL-5 / 40.01	89°	122°
		FL-5 / 40	106°	125°
		FL-5 / 41.01	109°	128°
		FL-5 / 41	73°	108°
		FL-5 / 42.01	83°	113°
		FL-5 / 42.02	98°	122°
		FL-5 / 42	86°	112°
		FL-5 / 43.01	97°	123°
		FL-5 / 43	114°	128°
		FL-5 / 44.01	101°	119°
		FL-5 / 44.02	115°	133°
		FL-5 / 44	128°	139°
		FL-5 / 45.01	98°	113°
		FL-5 / 45.02	106°	120°
		FL-5 / 45.03	110°	122°
		FL-5 / 45	113°	125°
		FL-5 / 46.01	115°	131°
		FL-5 / 46.02	119°	135°
		FL-5 / 46.03	100°	110°
		FL-5 / 46	105°	118°
		FL-5 / 47.01	111°	126°
		FL-5 / 47.02	115°	130°
		FL-5 / 47	117°	131°
		FL-5 / 48	120°	134°
		FL-5 / 49	123°	137°
		FL-5 / 50	127°	138°

BICO AUTO LIMPANTE
UM-5 RL-ES

SEXT. 1. 1/2"

ÂNGULOS DISPONÍVEIS: 0°; 15°; 30°; 40°; 45°; 50°; 60°; 80°; 100°; 120°; 130°

